5

WHAT IS CLAIMED IS:

An apparatus for switching communication data cells for a plurality of 1. communication ports in a communication network, said apparatus comprising:

a register block coupled to a first interconnect bus and having a memory for storing a connection setup notification;

a scheduler module coupled to said first interconnect bus and operably configured to determine scheduling of communication data cell transmissions to said communication ports;

a connection state unit coupled to a second interconnet bus and having a memory for storing connection information;

a look-up table coupled to said first interconnect and having a memory for storing a cross reference of a path identifier and an index into said connection state unit;

a processing unit coupled to said first interconnect bus for communication to said scheduler, said register block and said look-up table, and is operably configured to couple to said second interconnect bus for communication to said connector state unit and said communication ports, said processing unit is further between cells transmit communication data configured to operably

5

communication ports based on information collected from said register block, said look-up table, said connection state unit, and said scheduler module; and

a program memory unit coupled to said processing unit and having a memory for storing instruction executable by said processing unit

- The apparatus of Claim 1, wherein said program memory unit is further 2. coupled to a host processor, wherein said host processor supplies said executable instruction to said program memory unit memory.
- The apparatus of Claim 1, wherein said scheduler module is provided in 3. hardware.
- The apparatus of Claim 1, wherein said processing unit comprises a 4. packed data structure processor.
- The apparatus of Claim 1, wherein said connection information stored in 5. 15 said connection state unit includes traffic type, source and destination port identification and transmission parameters.

Patent Application

Atty . Docket Number: TI-32580

6. The apparatus of Claim 5, wherein said transmission parameters include

virtual path translation information, cell rates for programming said scheduler

module, and operation and maintenance configuration parameters.

5

10

7. The apparatus of Claim 1, wherein said processing unit is further operably

configured to perform quality of service type functions based on a predetermined

traffic contract.

8. The apparatus of Claim 1, wherein said scheduler is implemented in

hardware managed by said processing unit writing to command registers

associated with said scheduler.

9. The apparatus of Claim 1 wherein said processing unit is further operably

configured to execute VPI/VCI look-ups.

15

5

- The apparatus of Claim 1 wherein said processing unit is further operably 10. configured to set-up and tear-down a connection.
- The apparatus of Claim 1 wherein said processing unit is further operably 11. configured to execute VP/VC translation.
- The apparatus of Claim 1 wherein said processing unit is further operably 12. configured to execute traffic shaping.
- The apparatus of Claim 1 wherein said processing unit is further operably 13. configured to execute operation and maintenance processing.
- The apparatus of Claim 1 wherein said processing unit is further operably 14. configured to update ATM layer statistics.

15

5

A system for switching communication data cells for a plurality of 15. communication ports in a communication network, said system comprising:

a register block coupled to a first interconnect bus and having a memory for storing a connection setup notification;

a scheduler module coupled to said first interconnect bus and operably configured to determine scheduling of communication data cell transmissions to said communication ports;

a connection state unit coupled to a second interconnect bus and having a memory for storing connection information;

a look-up table coupled to said first interconnect and having a memory for storing a cross reference of a path identifier and an index into said connection state unit;

a processing unit coupled to said first interconnect bus for communication to said scheduler, said register block and said look-up table, and is operably configured to couple to said second interconnect bus for communication to said connector state unit and said communication ports, said processing unit is further transmit communication data cells configured operably communication ports based on information collected from said register block, said look-up table, said connection state unit, and said scheduler module;

15

a host interface unit for interfacing a host processor with said connection

state unit and said register block, wherein said connection setup notification is

loaded into said register block from an indication from said host processor, and

wherein said connection information is loaded into said connection state unit from

an indication from said host processor; and

a program memory unit coupled to said processing unit and having a

memory for storing instructions executable by said processing unit.

16. The system of Claim 15, wherein said program memory unit is further

coupled to said host processor, wherein said host processor supplies said

executable instruction to said program memory unit memory.

17. The system of Claim 15, wherein said scheduler module is provided in

hardware.

18. The system of Claim 15, wherein said processing unit comprises a packed

52

data structure processor.

JW 102521.00159 JWDOCS 2641039v1

5

19. The system of Claim 15, wherein said connection information stored in

said connection state unit includes traffic type, source and destination port

identification and transmission parameters.

20. The system of Claim 15, wherein said transmission parameters include

virtual path translation information, cell rates for programming said scheduler

module, and operation and maintenance configuration parameters.

21. The system of Claim 15, wherein said processing unit is further operably

configured to perform quality of service type functions based on a predetermined

traffic contract.

22. The system of Claim 15, wherein said scheduler is implemented in

hardware managed by said processing unit writing to command registers

associated with said scheduler.

5

- 23. The system of Claim 15, wherein said processing unit is further operably configured to execute VPI/VCI look-ups.
- 24. The system of Claim 15, wherein said processing unit is further operably configured to set-up and tear-down a connection.
- 25. The system of Claim 15, wherein said processing unit is further operably configured to execute VP/VC translation.
- 26. The system of Claim 15, wherein said processing unit is further operably configured to execute traffic shaping.
- 27. The system of Claim 15, wherein said processing unit is further operably configured to execute operation and maintenance processing.

28. The system of Claim 15, wherein said processing unit is further operably configured to update ATM layer statistics.